



NEW PRODUCT ANNOUNCEMENT

7595 GADSDEN HWY. ♦ TRUSSVILLE, ALABAMA 35173 ♦ PH: (205) 655-3271 ♦ FAX: 1-800-654-5980 ♦ email:sales@amerex-fire.com

RUGGED

- 5 Year Warranty
- All Metal Valve Construction
- Rust free aluminum cylinders
- Durable High Gloss Polyester Powder Paint
- Temperature Range:
-22°F to 120°F (-30°C to 49°C)

USER FRIENDLY

- Meets Many Hospital Medical Equipment Requirements
- Stainless Steel Pull Pin
- Model 320NM is Independently Tested and Approved for use in MRI Facilities to 11.7 Tesla
- Model 320NM Sanitary White Paint Finish (easy to clean)
- Bar Coded and Bi-lingual Labels

USER FRIENDLY

- Vehicle Bracket Model 896 Available for Model 320 only.
(DO NOT USE the Model 896 bracket in MRI or Non-Magnetic environments)



Model 320

(USES 16591 HANGER - INCLUDED)



**Model 320NM
NON-MAGNETIC**

MRI SAFE TO 11.7 TESLA
(USES 22885 HANGER - INCLUDED)

CARBON DIOXIDE is discharged as a white cloud of “snow” which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

Non-Magnetic model available (Model 320NM - Tested to 11.7 Tesla)

AGENT TYPE	CARBON DIOXIDE	
VALVE TYPE	CHROME PLATED BRASS	
DESIGN	HORN	
MODEL NUMBER	320	320NM
UL RATING	2B:C	2B:C
CAPACITY (LBS.)	2.5	2.5
SHIPPING WT. (LBS.)	8.9	8.9
HEIGHT (IN.)	13.25	13.25
WIDTH (IN.)	7.25	7.25
DEPTH (IN.)	4.38	4.38
RANGE (INITIAL- FT)	3 - 8	3 - 8
DISCHARGE TIME (SEC.)	9	9
FM APPROVED	NO	NO
INCLUDED BRACKET	WALL	WALL

**Manufactured and Tested to ANSI/UL
Standards
Complies with NFPA 10 Standard
ISO-9001 / ISO-14001 Certified
UL LISTED**

CONFORMS TO TEST STANDARDS:

CAN/ULC-S503 - ANSI/UL154 &
CAN/ULC-S508 - ANSI/UL711