# **PURPLE K DRY CHEMICAL**

**PURPLE K** extinguishers contain specially fluidized and siliconized potassium bicarbonate dry chemical which is particularly effective on Class B flammable liquids and pressurized gases. It is electrically non-conductive. **PURPLE K** has been the choice of oil, gas, chemical and utilities industries as the preferred fire-fighting agent.

### RUGGED

- 6-Year Manufacturer's Warranty
- Stored Pressure Design
- Dependable Drawn-Steel Cylinders
- Durable High-Gloss Polyester Powder Paint
- All-Metal Valve Construction

#### **BRASS VALVE**-HEAVY DUTY

- · Chrome-Plated Brass Valve Body
- Stainless-Steel Handle & Lever

# ALUMINUM VALVE— LIGHT TO MEDIUM DUTY

- Anodized Aluminum Valve Body
- · Anodized Aluminum Handle & Lever
- Temperature Range -65°F to 120°F

### **OPTION**

- USCG Approved with Bracket Listed on UL Label
- Chrome Cylinders (See Chart Below)

### **USER FRIENDLY**

- Easy and Economical to Maintain and Service
- Large Loop Pull Pin
- QR Coded and Bilingual Labels

## MANUFACTURED AND TESTED TO ANSI/UL STANDARDS

COMPLIES WITH NFPA 10 STANDARD ISO-9001/ ISO-14001 CERTIFIED ULLISTED

#### **CONFORMS TO TEST STANDARDS:**

CAN/ULC-S504 - ANSI/UL299 & CAN/ULC-S508 - ANSI/UL711







### LARGEST SELECTION OF SIZE AND EXTINGUISHER OPTIONS AVAILABLE.

	1		,				
AGENT TYPE	PURPLE K DRY CHEMICAL						
VALVE TYPE	ANODIZED ALUMINUM				CHROME PLATED BRASS		
DESIGN	NOZZLE			HOSE & NOZZLE			
MODEL NUMBER	376T	377	B410T	B479/B479T	A413	B460	415
UL & ULC RATING	2B:C	10B:C	10B:C	30B:C	120B:C	80B:C	120B:C
CAPACITY (LBS.)	1	2.5	2.5	5	20	10	20
SHIPPING WT. (LBS.)	2.25	4.625	5.5	9.5	36.4	19.5	38
HEIGHT (IN.)	10.25	14.69	15.5	15.25	24	20.5	24
WIDTH (IN.)	3.94	6.06	5.75	7.25	10.25	8.75	10.25
DEPTH (IN.)	2.63	3	3	4.25	7	5	7
RANGE (INITIAL- FT.)	5-8	5-8	9-15	12-18	15-21	15-21	15-21
DISCHARGE TIME (SEC.)	8.5	8.5	9.5	12	28	22	28
NOMINAL OPERATING PRESSURE	125 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG
OPTIONAL CHROME CYLINDER	YES	YES	YES				
INCLUDED BRACKET	VEHICLE	VEHICLE	VEHICLE	WALL/VEHICLE	WALL		

