

AMEREX WET CHEMICAL extinguishers are the best restaurant kitchen appliance hand-portable fire extinguishers you can purchase. Each model utilizes a specially blended potassium acetate base agent and has been tested and approved by UL for restaurant kitchen hazards. The recent trend to more efficient cooking appliances and use of vegetable-based cooking oils dictates the use of a hand-portable fire extinguisher with greater fire-fighting capacity and cooling effect to combat these very hot and difficult fires.

Available in two sizes; 6 liter or 2½ gallon—with attractive stainless-steel cylinders and easy-to-use hose-and-spray application nozzle. The superior fire-fighting capability of the Wet Chemical agent is placed exactly where you aim it with no dry chemical residue to clean up. The Models C260 and C262 are the ideal “KITCHEN USE” fire extinguishers. They supplement existing cooking equipment automatic system protection for an extra margin of safety.

RUGGED

- 5-Year Manufacturer’s Warranty
- Stored Pressure Design
- Polished Stainless-Steel Cylinders –USCG Models have Durable High-Gloss Polyester Powder Paint Coating
- All Stainless-Steel Valve Construction
- Exclusive Crevice-Free, Butt-Welded Cylinder
- Tested on Commercial Deep Fat Fryers to ANSI/UL711 Test Protocol and Safe to Use on Energized Electrical Appliances
- Class 2A Rated to Meet Fire Code Occupancy Hazard Requirements
- Temperature Range +40°F to 120°F

USER FRIENDLY

- Factory Charged
- Large Loop Stainless-Steel Pull Pin
- Agent Discharged as a Fine Mist– Helps Prevent Grease Splash and Re-flash While Cooling the Appliance
- Precise Extinguishing Agent Application
- QR Coded and Bilingual Labels

OPTION

- Models C260CG and C262CG are USCG Approved



Model C260

Model C262

"Amerex invented the K-Class Portable Fire Extinguisher—specifically designed and tested for commercial kitchen fires, and was the first to bring it to commercial kitchens."

Agent Type	Wet Chemical			
Model Number	C260	C262	C260CG	C262CG
UL & ULC Rating	2A:K		2A:K	
Capacity	6 Liter	2.5 Gal	6 Liter	2.5 Gal
Shipping WT. (Lbs)	22½	33½	22½	33½
Height (In.)	19	24½	19	24½
Width (In.)	9	9	9	9
Depth (In.)	7	7	7	7
Range (Initial-Ft)	10-12	10-12	10-12	10-12
Discharge Time (Sec.)	53	107	53	107
Included Bracket	Wall	Wall	Wall	Wall